Fichier:Programming Eaton DE Drive IMG 1808.jpg

No higher resolution available.

Programming_Eaton_DE_Drive_IMG_1808.jpg (640 × 480 pixels, file size: 96 KB, MIME type: image/jpeg)

Programming_Eaton_DE_Drive_IMG_1808

File history

Click on a date/time to view the file as it appeared at that time.

	Date/Time	Thumbnail	Dimensions	User	Comment
current	21:51, 30 October 2019		640 × 480 (96 KB)	Gareth Green (talk | contribs)	Programming_Eaton_DE_Drive_IMG_1808

You cannot overwrite this file.

File usage

The following page links to this file:

Programming Eaton DE Drive

Metadata

This file contains additional information, probably added from the digital camera or scanner used to create or digitize it. If the file has been modified from its original state, some details may not fully reflect the modified file.

Camera manufacturer	Apple
Camera model	iPhone XR
Exposure time	1/33 sec (0.03030303030303)
F Number	f/1.8
ISO speed rating	320
Date and time of data generation	19:49, 30 October 2019
Lens focal length	4.25 mm
Latitude	52° 35′ 33.65″ N
Longitude	1° 42′ 55.64″ E
Altitude	2.917 meters above sea level

Horizontal resolution	72 dpi
Vertical resolution	72 dpi
Software used	13.1.3
File change date and time	19:49, 30 October 2019
Exposure Program	Normal program
Exif version	2.31
Date and time of digitizing	19:49, 30 October 2019
Meaning of each component	1. Y 2. Cb 3. Cr 4. does not exist
APEX shutter speed	5.0592303599929
APEX aperture	1.6959938128384
APEX brightness	0.68141515487371
APEX exposure bias	0
Metering mode	Pattern
Flash	Flash did not fire, auto mode
DateTimeOriginal subseconds	276
DateTimeDigitized subseconds	276
Supported Flashpix version	0,100
Color space	sRGB
Sensing method	One-chip color area sensor
Scene type	A directly photographed image
Exposure mode	Auto exposure
White balance	Auto white balance
Focal length in 35 mm film	26 mm
Scene capture type	Standard
Speed unit	Kilometers per hour
Speed of GPS receiver	0
Reference for direction of image	True direction
Direction of image	130.80415324024
Reference for bearing of destination	True direction
Bearing of destination	130.80415324024
IIM version	2