Fichier:Test tutorial IMG 7710.JPG

Size of this preview:450 × 600 pixels.
Original file (768 × 1,024 pixels, file size: 143 KB, MIME type: image/jpeg)
Test_tutorial_IMG_7710

File history

Click on a date/time to view the file as it appeared at that time.

	Date/Time	Thumbnail	Dimensions	User	Comment
current	**17:23, 18 August 2022**		768 × 1,024 (143 KB)	Gareth Green (talk | contribs)	Test_tutorial_IMG_7710

You cannot overwrite this file.

File usage

There are no pages that link to this file.

Metadata

This file contains additional information, probably added from the digital camera or scanner used to create or digitize it. If the file has been modified from its original state, some details may not fully reflect the modified file.

Camera manufacturer	Apple
Camera model	iPhone 13 mini
Exposure time	1/100 sec (0.01)

F Number	f/1.6
ISO speed rating	40
Date and time of data generation	10:33, 15 August 2022
Lens focal length	5.1 mm
Latitude	52° 35′ 24.25″ N
Longitude	1° 42′ 34.69″ E
Altitude	15.998 meters above sea level
Orientation	Rotated 90° CCW
Horizontal resolution	72 dpi
Vertical resolution	72 dpi
Software used	15.6
File change date and time	10:33, 15 August 2022
Y and C positioning	Centered
Exposure Program	Normal program
Exif version	2.32
Date and time of digitizing	10:33, 15 August 2022
Meaning of each component	1. Y 2. Cb 3. Cr 4. does not exist
APEX shutter speed	6.6438561907444
APEX aperture	1.3561438092556
APEX brightness	4.8156702496225
APEX exposure bias	0
Metering mode	Pattern
Flash	Flash did not fire, compulsory flash suppression
DateTimeOriginal subseconds	844
DateTimeDigitized subseconds	844
Supported Flashpix version	0,100
Color space	Uncalibrated
Sensing method	One-chip color area sensor
Scene type	A directly photographed image
Exposure mode	Auto exposure
White balance	Auto white balance
Focal length in 35 mm film	26 mm
Scene capture type	Standard
Speed unit	Kilometers per hour
Speed of GPS receiver	0
Reference for direction of image	True direction
Direction of image	148.8539122569
Reference for bearing of destination	True direction
Bearing of destination	148.8539122569